

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A07105 NATIONAL GUARDS 620 ADHESIVE 20n12

Material number : 00000000001036726

#### Manufacturer or supplier's details

Company : National Guards

Address : 6900 Washington Blvd Montebello, CA 90640

Telephone : (800) 736-7606

<b>Emergency telephone numbers</b>	<b>CHEM-TEL INC.</b>
<b>For SDS Information</b>	: (800) 255-3924 or (813) 248-0585
<b>For a Medical Emergency</b>	: (800) 255-3924 or (813) 248-0585
<b>For a Transportation Emergency</b>	: (800) 255-3924 or (813) 248-0585

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	off-white
Odour	acetone-like

#### GHS Classification

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

#### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear eye protection/ face protection.  
P280 Wear protective gloves.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

P501 Dispose of contents/container in accordance with local regulation.

## Potential Health Effects

### Carcinogenicity:

#### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical Name	CAS-No.	Concentration [%]
butane	106-97-8	>= 30 - < 50
cyclohexane	110-82-7	>= 20 - < 30

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

acetone	67-64-1	>= 20 - < 30
propane	74-98-6	>= 5 - < 10

### SECTION 4. FIRST AID MEASURES

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Get medical attention if irritation develops and persists.  
Wash contaminated clothing before re-use.  
Wash off immediately with plenty of water for at least 15 minutes.
- In case of eye contact : Remove contact lenses.  
Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Keep respiratory tract clear.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Refer to protective measures listed in sections 7 and 8.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- Environmental precautions : Prevent further leakage or spillage.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Always replace cap after use.  
Do not breathe vapours or spray mist.  
Provide sufficient air exchange and/or exhaust in work rooms.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep in a dry, cool and well-ventilated place.
- Materials to avoid : Oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0
cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m <sup>3</sup>	NIOSH REL
		TWA	300 ppm 1,050 mg/m <sup>3</sup>	OSHA Z-1
		TWA	300 ppm 1,050 mg/m <sup>3</sup>	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm	NIOSH REL

**SAFETY DATA SHEET****A07105 NATIONAL GUARD 620 ADHESIVE 20n12**

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

			590 mg/m3	
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0

**Biological occupational exposure limits**

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Remarks : Skin should be washed after contact. For prolonged or repeated contact use protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Safety glasses  
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : General industrial hygiene practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Aerosol containing a liquefied gas

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

Colour	:	off-white
Odour	:	acetone-like
Odour Threshold	:	no data available no data available
pH	:	not applicable
Melting point/freezing point	:	no data available
Boiling point	:	no data available
Flash point	:	not applicable
Evaporation rate	:	no data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	no data available
Relative vapour density	:	no data available
Density	:	0.814 g/cm <sup>3</sup>
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		
Viscosity, kinematic	:	no data available
Heat of combustion	:	42.48 kJ/g

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. No decomposition if stored and applied as directed.
Conditions to avoid	:	Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SAFETY DATA SHEET**  
**A07105 NATIONAL GUARD 620 ADHESIVE 20n12**

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Components:**

**butane:**

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 rat: 1,355 mg/l

**cyclohexane:**

Acute oral toxicity : LD50 Oral rat: 12,705 mg/kg

Acute inhalation toxicity : LC50 rat: 13,900 mg/l  
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal rabbit: > 2,000 mg/kg

**acetone:**

Acute oral toxicity : LD50 rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 rat: 132 mg/l  
Exposure time: 3 h

LC50 rat: 50.1 mg/l

Acute dermal toxicity : LD50 guinea pig: > 7,426 mg/kg

LD50 rabbit: > 7,426 mg/kg

**propane:**

Acute inhalation toxicity : LC50 mouse: 1,237 mg/l  
Exposure time: 2 h

LC50 rat: 658 mg/l  
Exposure time: 4 h

LC50 rat: 1,355 mg/l

**Skin corrosion/irritation**

**Product:**

Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

**SAFETY DATA SHEET**  
**A07105 NATIONAL GUARD 620 ADHESIVE 20n12**

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

Remarks: May cause irreversible eye damage.

**Respiratory or skin sensitisation**

no data available

**Germ cell mutagenicity**

no data available

**Carcinogenicity**

no data available

**Reproductive toxicity**

no data available

**butane:**  
**cyclohexane:**  
**acetone:**  
**propane:**

**STOT - single exposure**

no data available

**STOT - repeated exposure**

no data available

**Aspiration toxicity**

no data available

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Remarks: no data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

no data available

**Persistence and degradability**

no data available

**Bioaccumulative potential**

**Product:**

Partition coefficient: n- : Remarks: no data available  
octanol/water

**Components:**

**butane :**  
Partition coefficient: n- : Pow: 2.89  
octanol/water



# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

**cyclohexane :**  
Partition coefficient: n- : log Pow: 3.44  
octanol/water

### Mobility in soil

no data available

### Other adverse effects

no data available

#### **Product:**

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations. Do not contaminate ponds, waterways or ditches with chemical or used container. The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Do not burn, or use a cutting torch on, the empty drum. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12

Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity
---

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
cyclohexane	110-82-7	1000	4010

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:  
cyclohexane 110-82-7 24.9355 %

**California Prop 65** WARNING! This product contains a chemical known to the State of California to cause cancer.  
benzene 71-43-2  
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.  
benzene 71-43-2

#### The components of this product are reported in the following inventories:

**TSCA** On TSCA Inventory  
**DSL** This product contains one or several components that are not on the Canadian DSL nor NDSL.  
**AICS** On the inventory, or in compliance with the inventory  
**NZIoC** Not in compliance with the inventory  
**PICCS** On the inventory, or in compliance with the inventory  
**IECSC** On the inventory, or in compliance with the inventory

#### Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

### SECTION 16. OTHER INFORMATION

# SAFETY DATA SHEET

## A07105 NATIONAL GUARD 620 ADHESIVE 20n12


Version 1.0

Revision Date 05/28/2015

Print Date 07/14/2015

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>4</b>
<b>PHYSICAL HAZARD</b>	<b>2</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

### OSHA GHS Label Information:

Hazard pictograms :



Signal word :

**Danger:**

Hazard statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements :

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/ face protection. Wear protective gloves.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.  
**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

Version:	1.0
Revision Date:	05/28/2015
Print Date:	07/14/2015

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.